AMENDMENTS TO THE CLAIMS

1. (Currently Amended) An apparatus for forming a beam in a base station, comprising:

a plurality of channel cards for processing and outputting signals to be transmitted to each channel;

a signal synthesizer/distributor for synthesizing the signals from the channel cards and compensating phases of the signals;

at least one channel controller for controlling beams of the signals from the signal synthesizer/distributor according to a demand of a mobile communication terminal, and outputting the controlled beam signals;

at least one middle frequency generating block for receiving the signals from the at least one channel controller and synthesizing the signals in each frequency to generate middle frequency signals;

at least one transmitter for converting the middle frequency signals received from the at least one middle frequency generating block into signals in a transmitting band;

a <u>Radio Frequency Block (RFB)</u> for amplifying the signals from the at least one transmitter into signals in an output band and controlling phases of transmitting and receiving signals; and

an antenna connection block for switching the amplified signals to corresponding antennas of the RFB so that beams can be generated.

2. (Original) An apparatus for forming a beam in a base station, comprising:
a plurality of transmitters for transmitting signals, the signals being controlled in
beam form according to the number of users in the base station;

a coupling block for receiving the signals from the transmitters and transmitting the received signals to an antenna side;

a switching controlling block for receiving the signals from the coupling block and switching the received signals according to the controlled results to output the

Attorney Docket No.: 678-628 (P9479)

switched signals;

an amplifying block for amplifying the signals from said switching controlling block in a certain level and outputting the amplified signals; and

a plurality of matrix buffers for receiving the signals from the amplifying block and switching the received signals to antennas to control beam shapes.